Technical Data Sheet

Aim.70

SKU: Aim.70

t: +(44) 020 7139 5129

enquiries@lightingoflondon.co

www.lightingoflondon.co




The Aim.70 is an elegantly designed downlight that can be used in both dry and humid interiors. Its sleek design, which features a deep black baffle and an ultra-slim aluminum powder-coated bezel, provides low glare and minimal architectural lighting.

The fitting allows for 20° of tilt and 180° of pan, enabling pinpoint accuracy of light. The Aim.70 also has an advanced heat sink that allows for cool running while requiring only 58mm height clearance. This fitting can accommodate beam angles of 15°, 24°, 36°, or 60°, with Correlated Colour Temperatures (CCT) of a warm 2700K or a cool white 4000K.

Product Category: Downlight

Material Anodised Aluminium Beam	n Angle 15°/24°/36°/60°
Lumen Output 780Lm Cut O	Out Ø 62mm
LED HonourTEK HRA0607 Fire &	& Acoustic Rated 60min
Lifespan >50,000 hours IP Rat	ating 54
CRI >95 Worki	sing Temperature -20°C - +40°C
Input Voltage DC Binnii	ing 1 SDCM
Power 9W 36V 250mA Colou	ur Temperature 2700K / 4000K
Power Factor >0.98 Stand	dard Finish Matt White / Matt Black

Dimensions



Lux Distribution Curve

