


Technical Data Sheet




The Focus.35 LED module is a masterpiece of modern engineering that is designed to elevate your lighting experience to the next level. With its magnetic connection to the Magtrak profile, this cutting-edge module boasts a superior appearance and installation that is sure to impress. The adjustable cable feature of this LED module allows the user to customize the angle of the light, providing comfortable spot lighting without any glare. Whether you're using it for professional lighting or decorative purposes, the Focus.35 LED module is the perfect solution for all your lighting needs. Moreover, this fitting is finished in a sleek black powder coating that adds an extra touch of style and elegance to your decor.

Material	Anodised Aluminium	Beam Angle	30°
Lumen Output	530Lm	Size	Ø 35 * 250mm
LED	CREE	Dimmable	TRIAC / DALI
Lifespan	>50,000 hours	IP Rating	20
CRI	>90	Working Temperature	-20°C - +40°C
Input Voltage	DC	Binning	1 SDCM
Power	5W 24V	Colour Temperature	2700K
Power Factor	>0.98	Standard Finish	Black Powder Coat

Light Distribution Curve



Dimensions



Lux Distribution Curve

3.28ft	194.000 fc	Δ	290.000 fc	1.19ft
1.0m	2,088.00 lx		3,121.00 lx	0.36m
6.56ft	48.500 fc		72.490 fc	2.38ft
2.0m	522.00 lx		780.30 lx	0.73m
9.84ft	21.550 fc		32.220 fc	3.57ft
3.0m	232.00 lx		346.80 lx	1.09m
13.12ft	12.120 fc		18.120 fc	4.77ft
4.0m	130.50 lx		195.10 lx	1.45m
16.40ft	7.760 fc		11.600 fc	5.96ft
5m	83.52 lx	7 1	124.80 lx	1.82m
Height	Avg E	Angle 20.58°	Max E	Diam.

LIGHTING OF LONDON Worlds End Studios, London, SW10 0RJ https://www.lightingoflondon.co, +(44) 020 7139 5129 ©All Rights Reserved