## **Technical Data Sheet**

## Follow.Me.R

SKU: Follow.Me.R

**t:** +(44) 020 7139 5129

⇔ enquiries@lightingoflondon.co

www.lightingoflondon.co




The Follow.Me.R recessed spotlight is highly versatile, offering almost complete directional control to the user. It comes with an adjustable cylindrical fitting that can point in a 355° horizontal range. If a 90° vertical spotlight is needed, it can be recessed back into its fitting to sit flush with the ceiling. The Follow.Me.R is designed to blend seamlessly into its surroundings.

This spotlight comes with three beam angle options- a sharp 15°, a generous 24° or a wider 36°, giving you ample options to highlight any wall or object with a warm 2700k glow.


 $\textbf{Product Categories: } Spotlights \ / \ Downlights$ 

Material	Anodised Aluminium	Beam Angle	15°/24°/36°
Lumen Output	403Lm	Cut Out	Ø 55mm
LED	TOYONIA DC500mA (Driver Supplied)	Fire & Acoustic Rated	60min
Lifespan	>50,000 hours	IP Rating	54
CRI	>90	Working Temperature	-20°- +40°C
Input Voltage	240V DC	Binning	1 SDCM
Power	8W	Colour Temperature	2700K
Power Factor	>0.98	Standard Finish	Matt White / Matt Black

## Dimensions



## **Lux Distribution Curve**



3.28ft	Emax	/\	E(Ix)	1.41ft
1.0m	2.450 lx	1	1.721 lx	0.43m
6.56ft				2.85ft
2.0m	612 lx		430 lx	0.87m
9.84ft				4.10ft
3.0m	271 lx		191 lx	1.25m
13.12ft				5.71ft
4.0m	152 lx		107 lx	1.74m
Height	Max E	Beam angle 24°	Ave E	Diameter

