

Technical Data Sheet

Linear.240

SKU: Linear.240.2700K.5.IP20 / Linear.240.2700K.5.IP66 Linear.240.2700K.10.IP20 / Linear.240.2700K.10.IP66 Linear.240.4000K.5.IP20 / Linear.240.4000K.5.IP66 Linear.240.4000K.10.IP20 / Linear.240.4000K.10.IP66



enquiries@lightingoflondon.co

W: www.lightingoflondon.co



Our linear range, consisting of an aluminium profile and LED strip light, is expertly designed to provide a long-lasting and high-quality lighting solution. The output and color rendering remain consistent over time, and the highlighting effect does not decay.

You can choose from 2700K or 4000K color temperature options, and 5m or 10m lengths. Additionally, we offer two IP ratings: IP20 or IP66.

We can customise our linear range to meet your specific needs and bring your vision to life.

Product Category: Linear

Input Voltage	DC 24V Constant Voltage	PCB Width	8mm
Power Per Metre	9.6W	Beam Angle	120°
Lumen Watts	81Lm	IP Rating	20 / 66
Lumen Per Metre	2700K - 850Lm / 4000K - 950Lm	Colour Temperature	2700K / 4000K
CRI	>90	Version	240 LEDS per metre
Cut Length	25mm	Length	5m / 10m