## **Technical Data Sheet**

# Profile.60

SKU: Pro.60

**t:** +(44) 020 7139 5129

enquiries@lightingoflondon.co

www.lightingoflondon.co



The Profile.60 is an elegantly designed downlight that can be used in both dry and humid interiors. Its sleek design, which features a deep black baffle and an ultra-slim aluminum powder-coated bezel, provides low glare and minimal architectural lighting.

The Profile.60 has a superior designed heat sink, allowing for cool running while only requiring 56mm height clearance.

The fitting comes can accommodate a 20° or 36° beam, with Correlated Colour Temperatures (CCT) of a warm 2700K.

**Product Category:** Downlight

Material	Anodised Aluminium	Beam Angle	20°/36°
Lumen Output	767Lm	Cut Out	Ø 50mm
LED	LUXEON COB 1202HD	Fire & Acoustic Rated	60min
Lifespan	>50,000 hours	IP Rating	54
CRI	>95	Working Temperature	-20°C - +40°C
Input Voltage	DC	Binning	1 SDCM
Power	8.75W 36V 250mA	Colour Temperature	2700K / 4000K
Power Factor	>0.98	Standard Finish	Matt White / Matt Black

### **Dimensions**

# \$ \\ \frac{1}{\sigma\_{58}} \\ \frac{1}{\sigma\_

### **Lux Distribution Curve**



