




## Profile.40

Product Category: *Downlight*

t: +(44) 020 7139 5129

e: [enquiries@lightingoflondon.co](mailto:enquiries@lightingoflondon.co)

w: [www.lightingoflondon.co](http://www.lightingoflondon.co)




The Profile.40 is an elegantly designed downlight that can be used in both dry and humid interiors. Its sleek design, which features a deep black baffle and an ultra-slim aluminum powder-coated bezel, provides low glare and minimal architectural lighting.

The Profile.40 has a superior designed heat sink, allowing for cool running while only requiring 49mm height clearance.

The fitting comes can accommodate a 15°, 24°, or 36° beam, with Correlated Colour Temperatures (CCT) of 2700K, 3000K, or 4000K.

Material	Aluminium	Beam Angle	15° / 24° / 36°
Lumen Output	160Lm	Luminous Efficacy	76lm / W
Power	2.1W 3V 700mA	IP Rating	54
Dimmable	Yes	Fire Rating	60min
CRI	>95	Driver Required	Yes
Power Factor	>0.98	Binning	2 - 3 SDCM
Size	40mm x 49mm	DALI Control	Yes (third party driver required)
Cut Out	35mm	Colour Temperature	2700K / 3000K / 4000K

### Dimensions



### Lux Distribution Curve

