



**POWERBANK250.**

|                            |                               |                                 |   |
|----------------------------|-------------------------------|---------------------------------|---|
| <b>Output Voltage</b>      | 25 - 42Vdc                    | <b>Efficiency</b>               | 85%                                     |
| <b>Output Current</b>      | 250mA                         | <b>In-Rush Current</b>          | Cold Start 1.54A                        |
| <b>Output Power</b>        | 6.25W - 10.5W                 | <b>Anti-Surge</b>               | L - N: 1.5kV                            |
| <b>Stroke Level</b>        | 8%                            | <b>Leakage Current</b>          | <0.25mA / 230Vac                        |
| <b>Dimming Range</b>       | 2 - 100%                      | <b>Working Temperature</b>      | 45°C - 85°C                             |
| <b>Dimming Interface</b>   | TRIAC Leading / Trailing Edge | <b>IP</b>                       | 20                                      |
| <b>Input Voltage Range</b> | 200 - 250Vac                  | <b>Over-Current Protection</b>  | Shut Down >102% (Auto Recovers)         |
| <b>Frequency</b>           | 50/60Hz                       | <b>Short Circuit Protection</b> | Shut Down Short Circuit (Auto Recovers) |
| <b>Input Current</b>       | <0.077A                       | <b>Over-Heat Protection</b>     | Shut Down >110°C (Auto Recovers)        |